




(Number of Conductors) N	X
(Pitch) P	0.50mm
(Total Pitch) Pt	X
(Total Length) L	X
(Film Length) IL	X
(Margin Width) M	X
(Total Width) W	X
(Strip Length) S1	X
(Strip Length) S2	X
(Stiffener) B1	X
(Stiffener) B2	X
(Slanting) A1	X
(Slanting) A2	X
(Terminal thickness) t	X
(Thickness) T	X

規格 (Spec)	0.5×X×X×C1 (X/X/X/X) (0.035×0.3) (0.06+0.06)UL20624		
4	補強板 (Connecting)	0.225 (深藍色)	
3	上絕緣膠 (Top Insulation)	0.06(白/印字white/printed)	
2	下絕緣膠 (Under Insulation)	0.06(白white)	
1	導體 (Conductor)	0.035×0.3 (鍍錫Tin Plating)	
ITEM	DESCRIPTION	SPECIFICATION	REMARK



东莞市高迪电子有限公司
Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS OTHERWISE STATED :
Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD. ANGEL'S

UNITS MM

DRAWN BY: Jack Lu
CHECKED BY: Jacky Chen
APPROVED BY: Tony Kao

DATE: 11/27/15

MAT'L		TITLE	FFC CABLE	
FINISH		MODLE	FFC CABLE	
SCALE	1 : 1	DWG NO.	FC11-xxx-S281	SIZE A4
SHEET NO.	1 of 1	PART NO.	FC11-xxx-S281	VER R