



SBC-240V4-31x-S271

鍍層厚度：

Blank : 1u"
2 : 15u"
3 : 30u"

PCB LAYOUT

SPECIFICATIONS

Electrical:

- 1.Rating: 3.0 A
- 2.Dielectric Withstand Voltage: 100V AC
- 3.Contact Resistance: 40 mΩ Max
- 4.Insulation Resistance: 100 MΩ Min

Material:

- 1.Housing: LCP,
- 2.Contact: PHOSPHOR BRONZE
- 3.Shell: SUS

Finish:

- 1.Contact: Plated Gold in Mating Area ;
Tin Plated on Solder Balls ;
Nickel under plated overall
- 2.Shell: Nickel under Plated surface layer



东莞市高迪电子有限公司
Dong Guan KDRR Electronic Switch JacK Co., Ltd.

TOLERANCE UNLESS OTHERWISE STATED :	Up to 5 ±0.2 Above 5 ~ 15 ±0.3 Above 15 ~ 30 ±0.4 Above 30 ~ 50 ±0.5 Angle ±0.3°	3RD. ANGEL'S	UNITS	MM
-------------------------------------	--	--------------	-------	----

DRAWN BY:	DATE	MAT'L	TITLE	CONNECTOR
Jack Lu	08/16/17			
CHECKED BY:	DATE	FINISH	MODLE	USB 3.1 TYPE C 夾板母座
Jacky Chen	08/16/17			
APPROVED BY:	DATE	SCALE	DWG NO.	SBC-240V4-31x-S271
Tony Kao	08/16/17	1 : 1		
		SHEET NO.	PART NO.	SBC-240V4-31x-S271

1	新增pcb layout	Jack	081617
ITEM NO.	DESCRIPTION	DRAWN	DATE