



MRUSB-5AB-RV5-x-S306

鍍層厚度：

Blank : 1u"

2 : 15u"

3 : 30u"

SPECIFICATIONS

Electrical:

- 1.Current Rating: 1.0A
- 2.Contact Resistance: 30 mΩ Max
- 3.Dielectric Withstanding Voltage: 100 V for 1 min
- 4.Insulation Resistance: 100 MΩ Min

Material:

- 1.Housing: LCP,UL 94V-0
- 2.Contact: Phosphor Bronze
- 3.Shell: SUS

Finish:

- 1.Contact: Plated Gold in Mating Area ;
Gold Plated on Solder Balls ;
Nickel under plated overall
- 2.Shell: Tin under Plated surface layer

P.C.B LAYOUT MOUNTING PATTEN



东莞市高迪电子有限公司

Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD.
ANGEL'S



UNITS

MM

DRAWN BY: Jack Lu
CHECKED BY: Jacky Chen
APPROVED BY: Tony Kao

DATE
04/22/15
DATE
04/22/15
DATE
04/22/15

MAT'L	TITLE	CONNECTOR
FINISH	MODLE	MICRO USB AB TYPE 反向牛角型
SCALE	DWG NO.	MRUSB-5AB-RV5-x-S306
SHEET NO.	PART NO.	MRUSB-5AB-RV5-x-S306

ITEM NO.	DESCRIPTION	DRAWN	DATE
2	更新尺寸及材質和鍍層	Jack	042215
1	新增鍍層厚度選項	Jack	042115