


MRUSB-5B-NE_x-S347


SHELL 鍍層:

TN

NI



P.C.B LAYOUT MOUNTING PATTERN



SPECIFICATIONS

Electrical:

- 1.Current Rating: 1.8A(pin1,5)Max, 1.0A(pin2,3,4)Max
- 2.Contact Resistance: 30 mΩ Max
- 3.Dielectric Withstanding Voltage:100 V AC for 1 min
- 4.Insulation Resistance: 100 MΩ Min

Mechanical:


- 1.Connector Mate and Unmate Force
Mate force: 3.57 kgf (Max)
Unmate force: 1.0 kgf (Min)

Material:

- 1.Housing: LCP
- 2.Contact: Phosphor Bronze
- 3.Shell: Brass

Finish:

- 1.Contact: Plated Gold in Mating Area ;
Gold Plated on Solder Balls ;
Nickel under plated overall
- 2.Shell: Tin or Nickel under Plated surface layer



东莞市高迪电子有限公司

Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS
OTHERWISE STATED :Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°3RD.
ANGEL'S

UNITS

MM

DRAWN BY: Jack Lu
CHECKED BY: Jacky Chen
APPROVED BY: Tony KaoDATE
07/17/17
DATE
07/17/17
DATE
07/17/17MAT'L
FINISH
SCALE
SHEET NO.TITLE
MODLE
DWG NO.
PART NO.CONNECTOR
MICRO USB 5BF 全貼無柱
MRUSB-5B-NE_x-S347
MRUSB-5B-NE_x-S347SIZE
A4
VER
A1

ITEM NO.	DESCRIPTION	DRAWN	DATE
2	新增外殼鍍層選項	Jack	071717
1	更新為A0版	Jack	062617