



MODEL NO.	DC-087-1.65
SCHEMATIC	
CENTER PIN	ø1.65mm

**\* MATERIAL**

- TERMINAL 1 : BRASS
- TERMINAL 2 : PHOSPHOR BRONZE
- TERMINAL 3 : BRASS
- HOUSING : PA66

**SPECIFICATION**

- Rating : DC 16V 2.5A
- Contact resistance : ≤ 50mΩ
- Insulation resistance : ≥ 100MΩ
- Withstand voltage : 500VAC
- Insertion and extraction force : 3-30N
- life test : 5,000 cycles



东莞市高迪电子有限公司  
Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS OTHERWISE STATED :

Up to 5 ±0.2  
Above 5 ~ 15 ±0.3  
Above 15 ~ 30 ±0.4  
Above 30 ~ 50 ±0.5  
Angle ±0.3°

3RD. ANGEL'S



UNITS

MM

DRAWN BY:	DATE
Jack Lu	08/12/14
CHECKED BY:	DATE
Jacky Chen	08/12/14
APPROVED BY:	DATE
Tony Kao	08/12/14

MAT'L		TITLE	JACK
FINISH		MODLE	DC JACK
SCALE	1 : 1	DWG NO.	DC-087-1.65
SHEET NO.	1 of 1	PART NO.	DC-087-1.65
		SIZE	A4
		VER	R1

ITEM NO.	DESCRIPTION	DRAWN	DATE
1	新增SPEC	Jack	081214