



DC MATE PLUG

MODEL NO.	DC-068DS
SCHEMATIC	
CENTER PIN	φ1.65mm

**\*MATERIAL**

- TERMINAL 1 : BRASS
- TERMINAL 2 : PHOSPHOR BRONZE
- TERMINAL 3 : BRASS
- SHIELD : PHOSPHOR BRONZE
- COVER : PA6T

**SPECIFICATION**

- Rating : DC 16V 2.5A
- Contact resistance : ≤50mΩ
- Insulation resistance : ≥100MΩ
- Withstand voltage : 500VAC
- Insertion and extraction force : 3-30N
- life test : 5,000 cycles



**东莞市高迪电子有限公司**  
Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS OTHERWISE STATED:  
 Up to 5 ±0.2  
 Above 5 ~ 15 ±0.3  
 Above 15 ~ 30 ±0.4  
 Above 30 ~ 50 ±0.5  
 Angle ±0.3

3RD. ANGEL'S



UNITS

MM

DRAWN BY:	DATE
Jack Lu	08/11/14
CHECKED BY:	DATE
Jacky Chen	08/11/14
APPROVED BY:	DATE
Tony Kao	08/11/14

MAT'L		TITLE	JACK
FINISH		MODLE	DC JACK
SCALE	1 : 1	DWG NO.	DC-068DS
SHEET NO.	1 of 1	PART NO.	DC-068DS
		SIZE	A4
		VER	A1

1	新增SPEC	Jack	081114
ITEM NO.	DESCRIPTION	DRAWN	DATE