


P.C.B LAYOUT

PS-D16Sx-S313

|    |          |
|----|----------|
| L  | SelfLock |
| NL | Nonlock  |



CIRCUIT DIAGRAM

**SPECIFICATIONS:**

- 1.RATING: 12V DC / 0.2A
- 2.CIRCUIT: 2C-2P
- 3.TIMING: NON-SHORTING
- 4.OPERATING FORCE: 250±100 gf

| NO. | PARTS    | MATERIALS       | Q'TY | FINISH            |
|-----|----------|-----------------|------|-------------------|
| 7   | CONTACT  | PHOSPHOR BRONZE | 1    | NATURAL           |
| 6   | SPRING   | SUS             | 1    | NATURAL           |
| 5   | LOCK PIN | SUS             | 1    | Ni PLATED         |
| 4   | TERMINAL | BRASS           | 1    | Ag PLATED OVER Ni |
| 3   | COVER    | PPA             | 1    | BLACK             |
| 2   | CASE     | PPA             | 1    | GREY              |
| 1   | KNOB     | PPA             | 1    | WHITE             |




**东莞市高迪电子有限公司**  
Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS OTHERWISE STATED:

Up to 5 ±0.2  
Above 5 ~ 15 ±0.3  
Above 15 ~ 30 ±0.4  
Above 30 ~ 50 ±0.5  
Angle ±0.3°

3RD. ANGEL'S



UNITS

MM

|              |          |           |          |               |
|--------------|----------|-----------|----------|---------------|
| DRAWN BY:    | DATE     | MAT'L     | TITLE    | SWITCH        |
| Jack Lu      | 11/15/16 |           |          |               |
| CHECKED BY:  | DATE     | FINISH    | MODLE    | PUSH SWITCH   |
| Jacky Chen   | 11/15/16 |           |          |               |
| APPROVED BY: | DATE     | SCALE     | DWG NO.  | PS-D16Sx-S313 |
| Tony Kao     | 11/15/16 | 1 : 1     |          |               |
|              |          | SHEET NO. | PART NO. | PS-D16Sx-S313 |
|              |          | 1 of 1    |          |               |

| ITEM NO. | DESCRIPTION | DRAWN | DATE   |
|----------|-------------|-------|--------|
| 1        | 更新材質        | Jack  | 111516 |