






P.C.B LAYOUT

SPECIFICATION

- 1.Rating : DC 30V 0.5A
- 2.Contact resistance : $\leq 50\text{m}\Omega$
- 3.Insulation resistance : $\geq 100\text{M}\Omega$
- 4.Withstand voltage : 500VAC
- 5.Insertion and extraction force : 3-30N
- 6.life test : 5,000 cycles

SCHEMATIC

PJ-3865D-S125	PJ-3863D-S125	PJ-3863AD-S125	PJ-3864D-S125	PJ-3864AD-S125

6	HOUSING	1	PA9T	
5	CURVE PIECE	1	BRASS	Au-Plating
4	CONTACT FOOT	1	SUS301	Au-Plating
3	CONTACT FOOT	1	SUS301	Au-Plating
2	CONTACT FOOT	1	SUS301	Au-Plating
1	SPRING PIECE	1	BE-CU	Au-Plating
NO.	DESCRIPTION	QTY	MATERIAL	PLATING



东莞市高迪电子有限公司
Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD.
ANGEL'S



UNITS

MM

DRAWN BY:	DATE	MAT'L	TITLE	JACK
Jack Lu	08/05/14			
CHECKED BY:	DATE	FINISH	MODLE	PHONE JACK
Jacky Chen	08/05/14			
APPROVED BY:	DATE	SCALE	DWG NO.	PJ-386xD-S125
Tony Kao	08/05/14	1 : 1	PART NO.	PJ-386xD-S125
		SHEET NO.	1 of 1	
				SIZE
				A4
				VER
				A0