









P.C.B LAYOUT
TOP VIEW



SCHEMATIC

PJ-S3212A



SPECIFICATION

- Rating : DC 30V, 0.5A ;
- Contact resistance : $\leq 30m\Omega$;
- Insulation resistance : $\geq 100M\Omega$;
- Withstand voltage : 500VAC ;
- Insertion and extraction force : 3-30N;
- life test : 5,000 cycles °

⑥	BUSHING	1	BRASS	Au-Plating
⑤	HOUSING	1	PA9T	
④	4# CONTACT FOOT	1	PHOSPHOR BRONZE	Au-Plating
③	3# CONTACT FOOT	1	PHOSPHOR BRONZE	Au-Plating
②	2# CONTACT FOOT	1	PHOSPHOR BRONZE	Au-Plating
①	1# CONTACT FOOT	1	PHOSPHOR BRONZE	Au-Plating
NO.	DESCRIPTION	QTY	MATERIAL	PLATING



东莞市高迪电子有限公司

Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD.
ANGEL'S



UNITS

MM

DRAWN BY:	DATE	MATL	TITLE	JACK
Jack Lu	11/21/19			
CHECKED BY:	DATE	FINISH	MODLE	PHONE JACK
Jacky Chen	11/21/19			
APPROVED BY:	DATE	SCALE	DWG NO.	PJ-S3212A-S124
Tony Kao	11/21/19	1 : 1	PART NO.	PJ-S3212A-S124
		SHEET NO.	1 of 1	
				SIZE A4
				VER R