






PRODUCT IMAGE

SCHEMATIC

P.C.B LAYOUT MOUNTING PATTERN



SPECIFICATIONS:

CONTACT RATING : 3 AMPS @ 120 V AC or 28 V DC.

1.5 AMPS @ 250 V AC or 0.4 VA AMPS @ 20 V AC or DC.

ELECTRICAL LIFE : 6,000 make-and-break cycles at full load.

CONTACT RESISTANCE : 20 mΩ max. initial @ 2-4 VDC

100 mA , for both coin silver and gold plated contacts.

INSULATION RESISTANCE : 1,000 MΩ min

DIELECTRIC STRENGTH : 1,000 V RMS @ sea level.

OPERATING TEMPERATURE : -30°C to 130°C

MTAERIALS:

CASE : Dially phthalate (DAP)(UL-94V-0)

ACTUATOR : Nylon , black standard.

BUSHING : Brass, nickel plated.

HOUSING : Stainless steel.

TERMINAL/CONTACT : Brass , witch silver or gold plated.

or gold over silver

SWITCH SUPPORT : Brass , tin plated.

ModelNo.	switching position		
RS-81	ON	NONE	ON
RS-82	ON	OFF	ON
RS-83	ON	NONE	(ON)
Tem Comm.	2-3	OPEN	2-1



TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD.
ANGEL'S



UNITS

MM

DRAWN BY:	DATE	MAT'L	TITLE	SWITCH
Jack Lu	08/21/14			
CHECKED BY:	DATE	FINISH	MODLE	TOGGLE ROCKER SWITCH
Jacky Chen	08/21/14			
APPROVED BY:	DATE	SCALE	DWG NO.	RS-81-RS5
Tony Kao	08/21/14	1 : 1		
		SHEET NO.	PART NO.	RS-81-RS5
		1 of 1		
				SIZE A4
				VER R3