





CIRCUIT DIAGRAM



P.C.B LAND PATTERN



SPECIFICATIONS

Rating	0.05A 12V DC
Insulation Resistance	50M Ω Min.
Dielectric Withstanding Voltage	AC 250 V(50Hz)1min
Contact Resistance	100m Ω Max.
Operating Force	180 $\pm$ 30gf
Operating Life	100,000 cycles

E	THERMINAL	2	PHOSPHOR BRONZE	Ag plated
D	CONTACT	3	STAINLESS STEEL	Ag plated
C	COVER	1	PHOSPHOR BRONZE	
B	BASE	1	LCP	Black
A	STEM	1	LCP	Black
NO.	DESCRIPTION	QTY	MATERIAL	PLATING



东莞市高迪电子有限公司
Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 $\pm$ 0.2
Above 5 ~ 15 $\pm$ 0.3
Above 15 ~ 30 $\pm$ 0.4
Above 30 ~ 50 $\pm$ 0.5
Angle $\pm$ 0.3°

3RD.
ANGEL'S



UNITS

MM

DRAWN BY: Jack Lu
CHECKED BY: Jacky Chen
APPROVED BY: Tony Kao

DATE: 11/07/13
DATE: 11/07/13
DATE: 11/07/13

MAT'L
FINISH
SCALE
SHEET NO.

TITLE: SWITCH
MODLE: TACT SWITCH
DWG NO.: TS-A28- 2-S246
PART NO.: TS-A28- 2-S246

SIZE: A4
VER: R