








DIMENSIONS



SCHEMATIC



P.C.B MOUNTING PATTERN



SPECIFICATIONS

Rating	DC 50V 0.5A
Circuit	2P - 2T
Contact Resistance	200mΩ Max.
Insulation Resistance	100MΩ Min.
Operating Force	200gf ±80gf
Operating Life (cycles)	10,000

Model No.	X(mm)
SS-22F07-G2	2mm
SS-22F07-G3	3mm
SS-22F07-G4	4mm
SS-22F07-G5	5mm
SS-22F07-G6	6mm
SS-22F07-G7	7mm
SS-22F07-G8	8mm
SS-22F07-G9	9mm
SS-22F07-G10	10mm
SS-22F07-G11	11mm
SS-22F07-G12	12mm
SS-22F07-G13	13mm

6	SPRING	2	STAINLESS STEEL	Natural
5	CONTACT	2	BRASS	Ag-Plated
4	TERMINAL	6	BRASS	Ag-Plated
3	BASE	1	PHENOLIC RESIN	Black
2	FRAME	1	SPCC	Ni-Plated
1	KNOB	1	POM	Black
NO.	DESCRIPTION	QTY	MATERIAL	REMARK



东莞市高迪电子有限公司
Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD.
ANGEL'S



UNITS

MM

DRAWN BY:	DATE	MAT'L	TITLE	SWITCH
Jack Lu	11/20/14			
CHECKED BY:	DATE	FINISH	MODLE	SLIDE SWITCH
Jacky Chen	11/20/14			
APPROVED BY:	DATE	SCALE	DWG NO.	SS-22F07-Gx-S191
Tony Kao	11/20/14	1 : 1		
		SHEET NO.	PART NO.	SS-22F07-Gx-S191
		1 of 1		