



SCHEMATIC

MODEL NO.	X(mm)
SS-12D03-G2-S191	2mm
SS-12D03-G3-S191	3mm
SS-12D03-G4-S191	4mm
SS-12D03-G5-S191	5mm
SS-12D03-G6-S191	6mm
SS-12D03-G7-S191	7mm
SS-12D03-G8-S191	8mm
SS-12D03-G9-S191	9mm

SPECIFICATIONS

Rating	0.3A 50V DC
FUNCTION	1P2T
Contact Resistance	200mΩ Max.
Insulation Resistance	100MΩ Min.
Operating Force	200gf ± 80gf
Operating Life	10,000 cycle

5	CONTACT CLIP	PBS STRIP	1	Ag PLATED
4	TERMINAL	BRASS	3	Ag PLATED
3	BASE	PHENOLIC RESIN	1	NATURAL
2	FRAME	STEEL STRIP	1	Ni PLATED
1	KNOB	POM	1	BLACK
NO.	PARTS	MATERIALS	QTY	FINISH

DRAWN BY:	DATE	MAT'L		TITLE	SWITCH	
Jack Lu	11/19/14					
CHECKED BY:	DATE	FINISH		MODLE	SLIDE SWITCH	
Jacky Chen	11/19/14					
		SCALE	1 : 1	DWG NO.	SS-12D03-Gx-S191	SIZE A4
APPROVED BY:	DATE	SHEET NO.	1 of 1	PART NO.	SS-12D03-Gx-S191	VER R2
Tony Kao	11/19/14					



东莞市高迪电子有限公司

Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5	± 0.2
Above 5 ~ 15	± 0.3
Above 15 ~ 30	± 0.4
Above 30 ~ 50	± 0.5
Angle	$\pm 0.3^\circ$

3RD.
ANGEL'S



UNITS

MM

TOLERANCE UNLESS
OTHERWISE STATED :