



1. 功能規格			
1.1 額定電壓		AC125V 1A/DC5V 30mA	1.5 自由位置 (FP) 10.4 ± 0.8mm
			1.6 動作位置 (OP) 8.8 ± 0.8mm
1.2 接觸電阻 (CR)	≤ 50mΩ (初始值)	1.7 行程 (PT)	
1.3 操作力 (OF)	30 ± 15gf	1.8 靈敏度 (BT)	
1.4 回彈力 (RF)			
2. 可靠度參數			
2.1 機械壽命	500,000 CYCLES	2.5 焊接方式	手工焊
2.2 電器壽命	10,000/500,000 CYCLES	2.6 適用溫度	-25° C ~ +65° C
2.3 絕緣電阻	≥ 100MΩ DC500V (初始值)	2.7 適用濕度	<85%RH
2.4 耐壓強度	AC500V 1 minute (初始值)		



Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS OTHERWISE STATED :	Up to 5	± 0.2
	Above 5 ~ 15	± 0.3
	Above 15 ~ 30	± 0.4
	Above 30 ~ 50	± 0.5
	Angle	± 0.3°

3RD.
ANGEL'S



UNITS

MM

DRAWN BY:

DATE _____

Frank Wu

06/01/17

Flank Wu

00/01/

CHECKED BY:

DATE _____

MAT'L.

TITLE

SWITCH

FINISH

MODLE

MICRO SWITCH

2 SCALE

1 : 1

DWG N°

D. DM1-01C

	SIZE
--	------

	VER
--	-----

	C
--	---