






PRODUCT IMAGE

SCHEMATIC

P.C.B LAYOUT MOUNTING PATTERN



SPECIFICATIONS:

CONTACT RATING : 3 AMPS @ 120 V AC or 28 V DC.
1.5 AMPS @ 250 V AC or 0.4 VA AMPS @ 20 V AC or DC.
ELECTRICAL LIFE : 6,000 make-and-break cycles at full load.
CONTACT RESISTANCE : 20 mΩ max. initial @ 2-4 VDC
100 mA , for both coin silver and gold plated contacts.
INSULATION RESISTANCE : 1,000 MΩ min
DIELECTRIC STRENGTH : 1,000 V RMS @ sea level.
OPERATING TEMPERATURE : -30°C to 130°C

MTAERIALS:

CASE : Dially phthalate (DAP)(UL-94V-0)
ACTUATOR : Nylon , black standard.
BUSHING : Brass, nickel plated.
HOUSING : Stainless steel.
TERMINAL/CONTACT : Brass , witch silver or gold plated.
or gold over silver
SWITCH SUPPORT : Brass , tin plated.

ModelNo.	switching position		
RS-81	ON	NONE	ON
RS-82	ON	OFF	ON
RS-83	ON	NONE	(ON)
Tem Comm.	2-3	OPEN	2-1

ITEM NO.	DESCRIPTION	DRAWN	DATE
3	更新pcb layout尺寸	Jack	082114
2	新增標誌	Jack	110713
1	標註尺寸&SPEC更新	FrankWu	111811

 东莞市高迪电子有限公司 Dong Guan KDRR Electronic Switch JacK Co., Ltd.				TOLERANCE UNLESS OTHERWISE STATED :		Up to 5 ±0.2 Above 5 ~ 15 ±0.3 Above 15 ~ 30 ±0.4 Above 30 ~ 50 ±0.5 Angle ±0.3°	3RD. ANGEL'S		UNITS	MM
---	--	--	--	-------------------------------------	--	--	--------------	--	-------	----

DRAWN BY:	DATE	MAT'L	TITLE	SWITCH
Jack Lu	08/21/14			
CHECKED BY:	DATE	FINISH	MODLE	TOGGLE ROCKER SWITCH
Jacky Chen	08/21/14			
APPROVED BY:	DATE	SCALE	DWG NO.	RS-81-RS5
Tony Kao	08/21/14	1 : 1		
		SHEET NO.	PART NO.	RS-81-RS5
		1 of 1		