



SCHEMATIC

1. SPECIFICATION.

RATINGS	5(2)A 125 / 250 V AC
TEMPERATURE	5GPA 125 / 250V AC 1 / 4 hp 250V AC
ELECTRONICAL LIFE	4A 30VDC 25T125 5E4 IP40 25T125 5E4 50~60Hz IP40
Insulation resistance	100 MΩ Min
Test voltage	AC 1000 / 1500V
Contact resistance	50 mΩ Max
Operating force	1.2 N Max
Release force	0.5 N Max
Operating position	15.2 ± 1.0mm

2. MATERIAL.

1	NC TERMINAL	Brass , Silver Plated
2	CASE	PBT (Black)
3	NO TERMINAL	Brass , Silver Plated
4	COVER	PBT (Black)
5	TERMINAL	Brass , Silver Plated
6	PLUNGER	PPS
7	PULL SPRING	SUS
8	MOVING ARM	SUS
9	MOVING PIECE	Tin-Brass
10	CONTACT	AgNi10
11	CONTACT	AgNi10



东莞市高迪电子有限公司

Dong Guan KDRR Electronic Switch Co., Ltd.

TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 ± 0.2
Above 5 ~ 15 ± 0.3
Above 15 ~ 30 ± 0.4
Above 30 ~ 50 ± 0.5
Angle ± 0.3°

3RD.
ANGEL'S



UNITS

MM

DRAWN BY: Jack Lu
CHECKED BY: Jacky Chen
APPROVED BY: Tony Kao
DATE: 07/24/15

MAT'L		TITLE	SWITCH
FINISH		MODLE	MICRO SWITCH
SCALE	1 : 1	DWG NO.	SM5-05N-50-S146
SHEET NO.	1 of 1	PART NO.	SM5-05N-50-S146

SIZE
A4
VER
R