










P.C.B LAYOUT
TOP VIEW

1. Rating : DC 24V 5.0A ;
2. Contact resistance : $\leq 30\text{m}\Omega$;
3. Insulation resistance : $\geq 100\text{M}\Omega$;
4. Withstand voltage : 500VAC ;
5. Insertion force : 3-30N;
extraction force : 3-30N;
6. life test : 5,000 cycles °

Model No.	DC-D303-x
SCHEMATIC	
CENTER PIN	ø2.00 mm
	ø2.50 mm

⑦	STOPPER	1	SUS	
⑥	SHELL	1	BRASS	Ni-Plating
⑤	GROUND	1	SUS	
④	PIN	1	BRASS	Ni-Plating
③	CONTACT FOOT	1	BRASS	Ni-Plating
②	SPRING	1	PHOSPHOR BRONZE	Ni-Plating
①	HOUSING	1	LCP	Black
NO.	DESCRIPTION	QTY	MATERIAL	PLATING

DRAWN BY:	DATE	MAT'L		TITLE	JACK	
Jack Lu	03/07/18					
CHECKED BY:	DATE	FINISH		MODLE	DC JACK	
Jacky Chen	03/07/18					
		SCALE	1 : 1	DWG NO.	DC-D303-x-S214	SIZE A4
APPROVED BY:	DATE					
Tony Kao	03/07/18	SHEET NO.	1 of 1	PART NO.	DC-D303-x-S214	VER R



东莞市高迪电子有限公司

Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS
OTHERWISE STATED

Up to 5	± 0.2
Above 5 ~ 15	± 0.3
Above 15 ~ 30	± 0.4
: Above 30 ~ 50	± 0.5
Angle	± 0.3

3RD.
ANGEL'S



UNITS

MM

ITEM NO.	DESCRIPTION	DRAWN	DATE
----------	-------------	-------	------