



CIRCUIT DIAGRAM

SPECIFICATIONS

Rating	DC 12V 50mA
Contact Resistance	150mΩ Max
Insulation Resistance	50MΩ Min
Operating Force	40 ±1.5gf
Life	50,000 cycles

NO.	PARTS	DATE	MAT'L	TITLE	QTY	FINISH
E	TERMINAL		PHOSPHOR BRONZE	4		Ag PLATED
D	CONTACT SPRING		PHOSPHOR BRONZE	1		Ag PLATED
C	COVER		PA46	1		BLACK
B	CASE		PPA	1		BLACK
A	KNOB		PA46	1		BLACK



东莞市高迪电子有限公司
Dongguan HODI Electronic Switch Jack Co., Ltd.

ITEM NO.	DESCRIPTION	DRAWN	DATE
1	零件图/零件图/K10306m	Jack	05/21/15
2	零件图/零件图/K10306m	Jack	05/21/15

TOLERANCE UNLESS OTHERWISE STATED:
 0.1 to 0.5 ±0.12
 Above 0.5 - 1.5 ±0.13
 Above 1.5 - 30 ±0.14
 Above 30 - 50 ±0.15
 Angle

DATE	FINISH	SCALE	DWG NO.	SIZE
05/21/15	SCALE	1:1		A4
05/21/15	SCALE	1:1		VER
05/21/15	SCALE	1:1		R2

