



PCB. 焊接尺寸图



CIRCUIT DIAGRAM

SPECIFICATIONS

Rating	DC 12V 50mA
Contact Resistance	150mΩ Max
Insulation Resistance	50MΩ Min
Operating Force	40 ±1.5gf
Life	50,000 cycles

NO.	PARTS	DATE	MAT'L	TITLE	QTY	FINISH
E	TERMINAL		PHOSPHOR BRONZE	4		Ag PLATED
D	CONTACT SPRING		PHOSPHOR BRONZE	1		Ag PLATED
C	COVER		PA46	1		BLACK
B	CASE		PPA	1		BLACK
A	KNOB		PA46	1		BLACK



东莞市高迪电子有限公司
Dongguan HODI Electronic Switch Jack Co., Ltd.

1	零件/物料/ITEM NO.	Jack	052115	TOLERANCE UNLESS OTHERWISE STATED: Above 5 - 15 ±0.13 Above 15 - 30 ±0.14 Above 30 - 50 ±0.15	3RD. ANGEL'S	UNITS	MM
2	零件/物料/ITEM NO.	Jack	052115		ANGEL'S		

DRAWN BY:	Jacky Chen	DATE:	05/21/15	MAT'L:		TITLE:	SWITCH
CHECKED BY:	Jacky Chen	DATE:	05/21/15	FINISH:		MODLE:	DETECTOR SWITCH
APPROVED BY:	Tony Kao	DATE:	05/21/15	SCALE:	1:1	DWG NO.:	
				SHEET NO.:	1 of 1	PART NO.:	

SIZE	A4
VER	R2