



SPECIFICATIONS

Rating	DC 12V 50mA
Contact Resistance	150mΩ Max
Insulation Resistance	50MΩ Min
Operating Force	40 ±1.5gf
Life	50,000 cycles

E	TERMINAL	PHOSPHOR BRONZE	4	Ag PLATED
D	CONTACT SPRING	PHOSPHOR BRONZE	1	Ag PLATED
C	COVER	PA46	1	BLACK
B	CASE	PPA	1	BLACK
A	KNOB	PA46	1	BLACK
NO.	PARTS	MATERIALS	QTY	FINISH



东莞市高迪电子有限公司
Dongguan KDR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS OTHERWISE STATED:		Up to 5mm	±0.2	3RD	UNITS	MM	APPROVED BY:		SHEET NO.	1 of 1	PART NO.	SIZE
		Above 5 - 15	±0.3	ANGELS			DATE		SCALE			A4
		Above 15 - 30	±0.4				DATE					VER
		Above 30 - 50	±0.5				DATE					R2
ITEM NO.	DESCRIPTION	DRAWN	DATE	CHECKED BY:			DATE		TITLE		DETECTOR SWITCH	
1	零件图	Jack	05/11/15	Jacky Chen			05/21/15		MODLE			
2	零件图	Jack	05/11/15	Tony Kao			05/21/15		DWG NO.			