








CIRCUIT DIAGRAM



SPECIFICATIONS

Rating	DC 12V 50mA
Contact Resistance	150mΩ Max
Insulation Resistance	50MΩ Min
Operating Force	40 ±1.5gf
Life	50,000 cycles



E	TERMINAL	PHOSPHOR BRONZE	4	Ag PLATED
D	CONTACT SPRING	PHOSPHOR BRONZE	1	Ag PLATED
C	COVER	PA46	1	BLACK
B	CASE	PPA	1	BLACK
A	KNOB	PA46	1	BLACK
NO.	PARTS	MATERIALS	QTY	FINISH



东莞市高迪电子有限公司
Dongguan KDR Electronic Switch Jack Co., Ltd.

ITEM NO.	DESCRIPTION	DRAWN	DATE	UP TO 5	3RD	UNITS	MM	CHECKED BY:	DATE	MATL.	TITLE	MODLE	DETECTOR SWITCH	SIZE
1	检测器开关模块	Jack	05/11/15	15 ±0.3	ANGEL'S			Jacky Chen	05/21/15	FINISH				A4
2	检测器开关模块	Jack	05/11/15	30 ±0.4				Jacky Chen	05/21/15	SCALE	1:1	DWG NO.		R2
3	检测器开关模块	Jack	05/11/15	50 ±0.5				Tony Kao	05/21/15	SHEET NO.	1 of 1	PART NO.		