



SPECIFICATIONS

Rating	DC 12V 50mA
Contact Resistance	150mΩ Max
Insulation Resistance	50MΩ Min
Operating Force	40 ±1.5gf
Life	50,000 cycles

NO.	PARTS	DATE	MAT'L	TITLE	QTY	FINISH
E	THERMINAL		PHOSPHOR BRONZE	4	Ag PLATED	
D	CONTACT SPRING		PHOSPHOR BRONZE	1	Ag PLATED	
C	COVER		PA46	1	BLACK	
B	CASE		PPA	1	BLACK	
A	KNOB		PA46	1	BLACK	

东莞市高迪电子有限公司
Dongguan GDDR Electronic Switch Jack Co., Ltd.

ITEM NO.	DESCRIPTION	DRAWN	DATE
1	物料/零件/MATERIAL	Jack	05/21/15
2	物料/零件/MATERIAL	Jack	05/21/15

TOLERANCE UNLESS OTHERWISE STATED:
 Up to 5 - ±0.2
 Above 5 - 15 ±0.3
 Above 15 - 30 ±0.4
 Above 30 - 50 ±0.5
 Angle ±0.5

3RD. ANGLES	UNITS	MM	APPROVED BY:	DATE	SHEET NO.	1 of 1	PART NO.	SIZE
3RD. ANGLES	UNITS	MM	Jacky Chen	05/21/15	SCALE	1 : 1	DWG NO.	A4
3RD. ANGLES	UNITS	MM	Tony Kao	05/21/15	SHEET NO.	1 of 1	PART NO.	R2