


SCHEMATIC (NON-SHORTING)



| X(mm) |
|-------|
| 2mm |
| 3mm |
| 4mm |
| 5mm |
| 6mm |
| 7mm |
| 8mm |
| 9mm |

SPECIFICATIONS

| | |
|-------------------------|--------------|
| Rating | DC 50V 0.5A |
| Circuit | |
| Contact Resistance | 200mΩ Max. |
| Insulation Resistance | 100MΩ Min. |
| Operating Force | 250gf ±100gf |
| Operating Life (cycles) | 10,000 |

| NO. | DESCRIPTION | QTY | MATERIAL | REMARK |
|-----|--------------|-----|-----------------|-----------|
| 7 | STEEL BALL | 1 | STAINLESS | Natural |
| 6 | SPRING | 1 | STAINLESS | Natural |
| 5 | CONTACT CLIP | 1 | PHOSPHOR BRONZE | Ag-plated |
| 4 | TERMINAL | 4 | BRASS | Ag-plated |
| 3 | BASE | 1 | PHENOLIC RESIN | Natural |
| 2 | FRAME | 1 | SPCC | Ni-Plated |
| 1 | KNOB | 1 | POM | Black |



东莞市高迪电子有限公司
DongGuan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS OTHERWISE STATED:
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3

3RD. ANGEL'S



UNITS MM

| | | | |
|---------------------------|------------------|--------------|-----------------------|
| DRAWN BY: Jack Lu | DATE 11/20/14 | MAT'L | TITLE SWITCH |
| CHECKED BY: Jacky Chen | DATE 11/20/14 | FINISH | MODLE SLIDE SWITCH |
| APPROVED BY: Tony Kao | DATE 11/20/14 | SCALE 1:1 | DWG NO. |
| SHEET NO. 1 of 1 | | PART NO. | |

| ITEM NO. | DESCRIPTION | DRAWN | DATE |
|----------|-------------|-------|----------|
| 3 | 新增SPEC | Jack | 11/20/14 |
| 2 | 更新材質 | Jack | 04/02/14 |
| 1 | 更新尺寸6.0改5.8 | Jack | 03/17/14 |

SIZE A4
VER R3