









DIM A	DIM B	DIM C
9.0	5.0	2.5
11.5	7.5	5.0
14.0	10.0	7.5
16.5	12.5	10.0



RECOMMENDED PCB LAYOUT
TOL:(±0.05)

性能:
 额定电流: 3.0A
 额定电压: 24V
 耐电压: 500V
 接触电阻: 30mΩ MAX
 绝缘电阻: 500MΩ
 工作温度: -40℃~+85℃
 塑件(材质): LCP, 耐高温260℃
 接触点(材质): 铜合金, 触点镀金3U'

②	HOUSING	1	LCP		BLACK
①	CONTACT A	2	PHOSPHOR BRONZE 0.20T	Au PLATED	
ITEM	PART NAME	Q'TY	MATERTAL	DESCRIPTION	REMARK

UNLESS OTHERWISE SPECIFIED TOLERANCES						东莞市高迪电子有限公司			
DECIMALS:		ANGLES:		DWG NO.		PART NAME:			
DIM	TOL	DIM	TOL	DESIGN:		PART NO.			
X.	±0.50	X.	±2°	CHECK:		REV. UNIT: SHEET:			
X.X	±0.30	X.X	±1°	APPROVED		A mm 1/1			
X.XX	±0.20	X.XX							
X.XXX	±0.10	X.XXX							