



REV.	ECN NO.	DESCRIPTION	DESIGN	DATE
A		INITIAL	Kai	2018.03.29

No. of Pins	Dimension			
	DIM.A	DIM.B	DIM.C	DIM.D
4	19.85	17.00	6.00	11.00
5	21.85	19.00	8.00	13.00
6	23.85	21.00	10.00	15.00
7	25.85	23.00	12.00	17.00
8	27.85	25.00	14.00	19.00
9	29.85	27.00	16.00	21.00
10	31.85	29.00	18.00	23.00
11	33.85	31.00	20.00	25.00
12	33.85	33.00	22.00	27.00

NOTE:

Material

Insulator:Nylon 9T(UL94V-0)

Contact:phosphor Bronze

Contact Plated:Gold over Nickel or Tin

Specification

Rated voltage: 12V 30V

Current rating: 5A 10A

instant CURRENT:12A

Contact Resistance: 30MΩ

Insulation Resistance:100MΩ

Dielectric Voltage:1000V

Operating Temperature: $-40^{\circ}\sim 105^{\circ}$

UNLESS OTHERWISE SPECIFIED TOLERANCES				东莞市高迪电子有限公司			
DECIMALS:		ANGLES:		DWG NO.		PART NAME:	
				DESIGN:		PART NO.	
DIM	TOL	DIM	TOL	CHECK:		REV. UNIT: SHEET:	
X.	±0.50	X.	±2°			A	mm
X.X	±0.30	X.X	±1°				1/1
X.XX	±0.20	X.XX	----				
X.XXX	±0.10	X.XXX	----	APPROVED			