

- D



Matching Plug



I JIN DOJODU KAPKINOVCE IMI

- Kn=KOHs 2.0 + Halogen free

Circuit Diagram A

NO.	DESCRIPTION	QTY	MATERIAL	REMARK
11	Mylar	1	Kapton	Yellow
10	Housing	1	PAIOT RES3NH+30MG UL 94V-0	Black
9	Molding	1	PAIOT RES3NH+30MG UL 94V-0	Black
7	Shunt terminal	1	Phosphor bronze, 0.20t	Gold Flash on contact over Nickel Plated. All
8	Shell	1	Phosphor bronze, 0.20t	Plating Ni .
6	Shunt terminal	1	Phosphor bronze, 0.20t	Gold Flash On Contact Area
5	Transfer Spring	1	Phosphor bronze, 0.20t	tin Plating
4	Ring spring	1	Phosphor bronze, 0.20t	on Solder
3	Ring spring	1	Phosphor bronze, 0.20t	Tail Area
2	Tip spring	1	Phosphor bronze, 0.25t	All over
1	Earth spring	1	Phosphor bronze, 0.20t	Nickel Plated

										东莞市高迪电子有限公司	
				Angle	±2°	DESIGN	李海鸥	2016.06.07		TITLE:	φ3.5mm PHONE JACK
				.x	±0.30	CHECK				MODEL NO.	PJR-D3156B-ABK7ASO2L-RH
				.xx	±0.25	APPROVAL				FILE NO.	Q/SST-QW-001A-0XXX
				.xxx	±0.10	SCALE: 3:1	UNIT:mm	A4	SHEET:1 of 1		
ECN NO.	REV	DATE	DESCRIPTION	CHANGE	APPRO.	GENERAL TOLERANCE UNLESS OTHERWISE NOTED					
	A-0	2016.06.07	NEW	李海鸥							