




A DETAIL COPLANARITY



RECOMMENDED
SOLDER PAD LAYOUT
(TOP VIEW)

SCHEMATIC

```

TERMINAL 1 :PHOSPHOR BRONZE
TERMINAL 2 :PHOSPHOR BRONZE
TERMINAL 3 :PHOSPHOR BRONZE
TERMINAL 4 :PHOSPHOR BRONZE
TERMINAL 5 :PHOSPHOR BRONZE
TERMINAL 10:BRASS
TERMINAL 11:BRASS
HOUSING :PA6T

```

- 1.Rating :DC 12V 1.0A
- 2.Contact resistance : $\leq 50\text{m}\Omega$
- 3.Insulation resistance : $\geq 100\text{M}\Omega$
- 4.Withstand voltage : 500VAC
- 5.Insertion and extraction force : 3-30N
- 6.life test : 5,000 cycles



东莞市高迪电子有限公司

Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS OTHERWISE STATED.

Up to 5	± 0.2
Above 5 ~ 15	± 0.3
Above 15 ~ 30	± 0.4
: Above 30 ~ 50	± 0.5
Angle	± 0.3

3RD.
ANGEL'S



UNITS

MM

DRAWN BY:	DATE
Jack Lu	11/03/15

CHECKED BY:	DATE
Jacky Chen	11/03/15

APPROVED BY:	DATE
Tony Kao	11/03/15

MAT'L

FINISH

SCALE

SHEET N

TITLE	JACK
-------	------

MODLE	PHONE JACK
-------	------------

DWG NO.	PJ-382xD
---------	----------

PART NO	PI-382xD
---------	----------

	SIZE
--	------

VER
