



安装孔尺寸图

配线图



电源参数: 12 (10) A 250V AC; 7 (7) A 250V AC; 8 A 250V AC;
16 A 125V AC; 18 A 125V AC
接触电阻: $\leq 50 \text{ m}\Omega$
绝缘电阻: $\geq 100 \text{ M}\Omega$
介电强度: 极与极 1500VAC, 极与壳 3000VAC
环境温度: T105
电气寿命: 1E4

8					TOLERANCE				
7					UNLESS SPECIFIED				
6					WITHIN 1.5mm : $\pm 0.1 \text{ mm}$	A	2012-8-13	初版	
5	SPRING	SUS	1	NATURAL	OVER 1.5mm : $\pm 0.2 \text{ mm}$	ISSUE	DATE	DESCRIPTIONS OF REVISION	APPD.
4	CAM STICK	SUS	1	NATURAL	TITLE : VERTICAL PUSH SWITCH			UNIT : mm	DRWG NO.:
3	CASE	PA66/BRASS STRIP	1	GREY/Ag PLATED	MODEL:			SCALE: 5:1	DWN.
2	COVER	PA66	1	BLACK	东莞市高迪电子有限公司			CHK'D	2012-8-13
1	KNOB	PA66/PBS C5210R-EH	1	WHITE/Ag CLAD				APPD.	2012-8-13
NO.	PARTS	MATERIALS	Q'TY						