






	X	Y
0.75~1.25	30.0+0.1	122.0+0.1
1.25~2.00	30.2+0.1	122.0+0.1
2.00~3.00	30.4+0.1	122.0+0.1

开孔尺寸



ON-OFF

Marking	x	0	1	2	3	4	5	7	8	9	B	C	E	F	G
柄	None	•	ON OFF	=	—	—	—	Front/后 Back/前	Front Back	强制 柔和	⬆ ⬆	RUN STOP	充电 弱磁	开关	⬆ ⬆

注： "•"□表示关键尺寸(3个)。

8					TOLERANCE UNLESS SPECIFIED				
7									
6					WITHIN 1.5mm : ±0.1mm OVER 1.5mm : ±0.2mm	A ISSUE	2012-8-13 DATE	初版	
5	SPRING	SUS	1	NATURAL				DESCRIPTIONS OF REVISION	APPD.
4	CAM STICK	SUS	1	NATURAL	TITLE : SWITCH		UNIT : mm	DRWG NO.:	
3	CASE	PA66/BRASS STRIP	1	GREY/Ag PLATED	MODEL:		SCALE: 5:1	DWN.	2012-8-13
2	COVER	PA66	1	BLACK				CHK'D	
1	KNOB	PA66/PBS C5210R-EH	1	WHITE/Ag CLAD				APPD.	2012-8-13
NO.	PARTS	MATERIALS	Q'TY		东莞市高迪电子有限公司				