



	X	Y
0.75~1.25	30.0±0.1	22.0±0.1
1.25~2.00	30.2±0.1	22.0±0.1
2.00~3.00	30.4±0.1	22.0±0.1

Marking	x	0	1	2	3	4	5	7	8	9	B	C	E	F	G
柄	None	•	ON OFF	=	—	○	○	Front/Back	Front/Back	强加 柔和	强加 柔和	RUN STOP	充电 放电	开关	○

注： "※"□表示关键尺寸(3个)。

8					TOLERANCE				
7					UNLESS SPECIFIED				
6					WITHIN 1.5mm : ±0.1mm	A	2012-8-13	初版	
5	SPRING	SUS	1	NATURAL	OVER 1.5mm : ±0.2mm	ISSUE	DATE	DESCRIPTIONS OF REVISION	APPD.
4	CAM STICK	SUS	1	NATURAL	TITLE : SWITCH				UNIT : mm
3	CASE	PA66/BRASS STRIP	1	GREY/Ag PLATED	MODEL:				DRWG NO.:
2	COVER	PA66	1	BLACK					SCALE: 5:1
1	KNOB	PA66/PBS C5210R-EH	1	WHITE/Ag CLAD					DWN.
NO.	PARTS	MATERIALS	Q'TY		东莞市高迪电子有限公司				2012-8-13
									CHK'D
									APPD.
									2012-8-13