



开孔尺寸



	X	Y
0.75~1.25	30.0+0.1	22.0+0.1
1.25~2.00	30.2+0.1	22.0+0.1
2.00~3.00	30.4+0.1	22.0+0.1

Marking	x	0	1	2	3	4	5	7	8	9	B	C	E	F	G
柄	None	•	ON OFF	=	-	○	○	Power/Off Back/On	Front Back	强 弱	强 弱	强 弱	强 弱	强 弱	强 弱

注： "□"表示关键尺寸(3个)。

NO.	PARTS	MATERIALS	Q'TY	TOLERANCE UNLESS SPECIFIED	DATE	DESCRIPTIONS OF REVISION	APPD.
8							
7							
6				WITHIN 1.5mm : ±0.1mm OVER 1.5mm : ±0.2mm	A	2012-8-13	初版
5	SPRING	SUS	1	NATURAL	ISSUE	DATE	DESCRIPTIONS OF REVISION
4	CAM STICK	SUS	1	NATURAL	TITLE : SWITCH		
3	CASE	PA66/BRASS STRIP	1	GREY/Ag PLATED	MODEL:		
2	COVER	PA66	1	BLACK	SCALE: 5:1		
1	KNOB	PA66/PBS C5210R-EH	1	WHITE/Ag CLAD	DWN.		
					CHK'D		
					APPD.		
					2012-8-13		
					2012-8-13		

东莞市高迪电子有限公司