




TS-A07GS-x-x-S126

Operating Force

Color:

W	Case:White	Knob:White
R	Case:Black	Knob:Red



CIRCUIT DIAGRAM

SPECIFICATIONS

Rating	DC 12V 50mA		
Contact Resistance	100mΩ Max.		
Travel	0.25 ± 0.1mm		
Operating Force	1 130±30gf	2 160±30gf	3 250±50gf
Operating Life(cycles)	50,000		30,000

P.C.B MOUNTING PATTERN DIMENSION

The following soldering patterns are recommended for reflow soldering



东莞市高迪电子有限公司

Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 ± 0.2
Above 5 ~ 15 ± 0.3
Above 15 ~ 30 ± 0.4
Above 30 ~ 50 ± 0.5
Angle ± 0.3°

3RD.
ANGEL'S



UNITS

MM

DRAWN BY: Jack Lu
CHECKED BY: Jacky Chen
APPROVED BY: Tony Kao

DATE
11/14/14
DATE
11/14/14
DATE
11/14/14

MAT'L
FINISH
SCALE

TITLE
MODLE
DWG NO.
PART NO.

SWITCH
TACT SWITCH
TS-A07GS-x-x-S126
TS-A07GS-x-x-S126

SIZE
A4
VER
R1

1	更新料號	Jack	111414
ITEM NO.	DESCRIPTION	DRAWN	DATE