






SPECIFICATIONS

1. RATING : 0.5mA 12VDC MAX .
2. CONTACT RESISTANCE : 100 mΩ MAX .
3. INSULATION RESISTANCE : 500 V DC , 100 MΩ MIN
4. OPERATING TEMPERATURE : -20℃ ~ 70℃ .
5. OPERATING FORCE : 160±50gf . 250±50gf
6. OPERATING LIFE : 100,000 CYCLES .




东莞市高迪电子有限公司

TITLE : ILLUMINATED TACTILE SWITCH

MODEL :

DRAWING NO. : _



UNIT : M M	DWN.	LSX	2015-02-18	GENERAL TOLERANCE	9				
SCALE : 5 : 1	CHK'D	LJ	2015-02-18	WITHIN 1.5mm±0.1mm	8				
LEVEL 1	REV R1	APPD.	2015-02-18	OVER 1.5mm±0.2mm	7				
					6	CAP	ABS/PC	1	SILVER /BLACK
					5	CONTACT	PBS	1	Ag CLAD
					4	TERMINAL	BRASS STRIP	4	Ag PLATED
					3	BASE	PA66	1	BLACK
					2	COVER	PET	1	NATURAL
					1	KNOB	PA66	1	WHITE
					NO.	PART NAME	MATERIAL	QTY.	FINISHING