




SBC-WP240M3-31x-S347

鍍層厚度:

Blank : 1u"
2 : 15u"
3 : 30u"



P.C.B LAYOUT MOUNTING PATTERN






SPECIFICATIONS

- Electrical:
- 1. Rating: 3.0A
 - 2.Contact Resistance: 40 mΩ Max
 - 3.Insulation Resistance: 100 MΩ Min
 - 4.Dielectric Withstanding Voltage: 100V AC

- Mechanical:
- 1.Connector Mate and Unmate Force
 - 1.1 Mate force: 5~20 N
 - 1.2 Unmate force: 8~20 N

- Material:
- 1.Housing: High-TEMP Plastic
 - 2.Contact: Copper Alloy
 - 3.Shell: SUS

- Finish:
- 1.Contact: Plated Gold in Mating Area ;
Tin Plated on Solder Balls ;
Nickel under plated overall
 - 2.Shell: Nickel under Plated surface layer



A1	GND	B12	GND
A2	SSTXP1	B11	SSRXP1
A3	SSTXN1	B10	SSRXN1
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	DP1	B7	DN2
A7	DN1	B6	DP2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A10	SSRXN2	B3	SSTXN2
A11	SSRXP2	B2	SSTXP2
A12	GND	B1	GND
PIN	SIGNAL NAME	PIN	SIGNAL NAME



东莞市高迪电子有限公司
Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS OTHERWISE STATED :

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD. ANGEL'S



UNITS

MM

DRAWN BY: Jack Lu
CHECKED BY: Jacky Chen
APPROVED BY: Tony Kao

DATE
03/11/19
DATE
03/11/19
DATE
03/11/19

MAT'L
FINISH
SCALE
SHEET NO.

TITLE
CONNECTOR
MODLE
DWG NO.
PART NO.

SIZE
A4
VER
R1

1	更新圖面	Jack	031119
ITEM NO.	DESCRIPTION	DRAWN	DATE