




SCHEMATIC

SPECIFICATIONS


1. RATING : 0.5mA 12VDC MAX .
2. CONTACT RESISTANCE : 100 m Ω MAX .
3. INSULATION RESISTANCE : 500 V DC , 100 M Ω MIN
4. OPERATING TEMPERATURE : -20 $^{\circ}$ C ~ 70 $^{\circ}$ C .
5. OPERATING FORCE : 160 $\pm$ 50gf . 250 $\pm$ 50gf
6. OPERATING LIFE : 100,000 CYCLES .

东莞市高迪电子有限公司

TITLE : TACTILE SWITCH

MODEL :

DRAWING NO. : _



UNIT : M M	DWN.	LSX	2015-02-18	GENERAL TOLERANCE	9				
SCALE : 5 : 1	CHK' D	LJ	2015-02-18	WITHIN 1.5mm $\pm$ 0.1mm	8				
LEVEL 1	REV R1	APPD.	2015-02-18	OVER 1.5mm $\pm$ 0.2mm	7				
					6	CAP	ABS/PC	1	SLIVER /BLACK
					5	CONTACT	PBS	1	Ag CLAD
					4	TERMINAL	BRASS STRIP	4	Ag PLATED
					3	BASE	PA66	1	BLACK
					2	COVER	PET	1	NATURAL
					1	NOB	PA66	1	WHITE
					NO.	PART NAME	MATERIAL	QTY.	FINISHING