







X=2-6
单位: mm



SCHEMATIC (NON-SHORTING)



P.C.B. LAYOUT
TOP VIEW

按键开关技术参数:

1. 额定负荷: DC 30V 50V 0.1A 0.5A
2. 接触阻抗: $\leq 50\text{m}\Omega$
3. 绝缘阻抗: DC 250V $\geq 100\text{m}\Omega$
4. 耐焊温度: $250\pm 5^{\circ}$ 5s
5. 使用寿命: 100,000 cycles
6. 使用温度: -25°C to 80°C
7. 使用湿度: $\leq 85\% \text{ RH}$
8. 操作力: 240gf $\pm$ 80gf
9. 功能选择: 复位/常开/常闭
10. 按压力可定制

8					TOLERANCE					
7					UNLESS SPECIFIED					
6	SPRING	STEEL WIRE	1	NATURAL	WITHIN 1.5mm : ±0.1mm	A	2012-11-06	初 版		
5	CONTACT CLIP	PBS C5210R-EH	2	Ag CLAD	OVER 1.5mm : ±0.2mm	ISSUE	DATE	DESCRIPTIONS OF REVISION		APPD.
4	BASE	PHENOLIC RESIN	1	NATURAL	TITLE : PUSH SWITCH			UNIT : mm	DRWG NO.:	
3	TERMINAL	BRASS STRIP	6	Ag PLATED OVER Ni PLATED	MODEL:			SCALE: 2:1	DWN.	2012-11-06
2	FRAME	Electrolytic strip	1	NATURAL	 东莞市高迪电子有限公司			CHK'D		2012-11-06
1	KNOB	PC	1	BLACK				APPD.		2012-11-06
NO.	PARTS	MATERIALS	Q'TY	FINISH						