







Technical drawing of a T-shaped part. The top flange has a width of 17 and a height of 7.5. The stem has a height of 9 and a width of 5.4. A dimension of 3 TRAVEL is indicated for the stem width. The drawing includes dashed lines for centerlines and a break symbol on the stem.



拨动开关侧拨技术参数:

1. 额定负荷: DC 30V 50V 0.3A 0.5A
2. 接触阻抗: $\leq 50\text{m}\Omega$
3. 绝缘阻抗: $\geq 100\text{m}\Omega$ DC500V
4. 耐焊温度: $250 \pm 5^\circ \text{C}$ 5s
5. 使用寿命: 10,000 cycles
6. 使用温度: -25°C to 80°C
7. 使用湿度: $\leq 85\% \text{ RH}$
8. 操作力 : 160gf 256gf 300gf 可定制
9. 手柄长度: 2mm-10mm 可定制

注：“*”表示关键尺寸(6个)

8				TOLERANCE UNLESS SPECIFIED					
7	STEEL BALL	STEEL	1	NATURAL					
6	SPRING	STEEL WIRE	1	NATURAL	WITHIN	A	2012-12-25	初板	
5	CONTACT CLIP	PBS STRIP	2	Ag PLATED	OVER	ISSUE	DATE	DESCRIPTIONS OF REVISION	APPD
4	TERMINAL	BRASS STRIP	10	Ag PLATED	TITLE: HORIZONTAL SLIDE SWITCH			UNIT : mm	DRWG NO.:
3	BASE	PHENOLIC RESIN	1	BLACK	MODEL:			SCALE: 2:1	DWN
2	FRAME	STEEL STRIP	1	Ni PLATED					2012-12-25
1	KNOB	POM	1	BLACK	 东莞市高迪电子有限公司			CHK'D	
NO.	PARTS	MATERIALS	QTY	FINISH				APPD	2012-12-25