


SCHMATIC (NON-SHORTING)

注: "*"表示关键尺寸 (6个)

- 拨动开关立式技术参数:
1. 额定负荷: DC 30V 50V 0.3A 0.5A
 2. 接触阻抗: ≤50mΩ
 3. 绝缘阻抗: ≥100mΩ DC500V
 4. 耐焊温度: 250±5° 5s
 5. 使用寿命: 10,000 cycles
 6. 使用温度: -25 ℃ to 80 ℃
 7. 使用湿度: ≤85% RH
 8. 操作力 : 160gf 256gf 300gf 可定制
 9. 手柄长度: 2mm-10mm 可定制

8					TOLERANCE							
7	STEEL BALL	STEEL	1	NATURAL	UNLESS SPECIFIED							
6	SPRING	STEEL WIRE	1	NATURAL	WITHIN	A	2012-10-28	初 版				
5	CONTACT CLIP	PBS STRIP	2	Ag PLATED	OVER	ISSUE	DATE	DESCRIPTIONS OF REVISION	APPD.			
4	TERMINAL	BRASS STRIP	8	Ag PLATED	TITLE : VERTICAL SLIDE SWITCH			UNIT : mm	DRWG NO.:			
3	BASE	PHENOLIC RESIN	1	NATURAL	MODEL:			SCALE: 3:1				
2	FRAME	STEEL STRIP	1	Ni PLATED	东莞市高迪电子有限公司					DWN.		2012-10-28
1	KNOB	POM	1	BLACK						CHK'D		2012-10-28
NO.	PARTS	MATERIALS	Q'TY	FINISH						APPD.		