








- 拨动开关立式技术参数:
1. 额定负荷:AC 125V 250V 3A 6A 10A
 2. 接触阻抗: ≤50mΩ
 3. 绝缘阻抗: ≥100mΩ DC500V
 4. 耐焊温度: 250±5° 5s
 5. 使用寿命: 10,000 cycles
 6. 使用温度: -25 ℃ to 80 ℃
 7. 使用湿度: ≤85% RH
 8. 操作力 :160gf 256gf 300gf 可定制
 9. 手柄长度:2mm-10mm 可定制

注: "*"表示关键尺寸 (6个)

8					TOLERANCE				
7	STEEL BALL	STEEL	1	NATURAL	UNLESS SPECIFIED				
6	SPRING	STEEL WIRE	1	NATURAL	WITHIN	A	2012-10-28	初 版	
5	CONTACT CLIP	PBS STRIP	2	Ag PLATED	OVER	ISSUE	DATE	DESCRIPTONS OF REVISION	APPD.
4	TERMINAL	BRASS STRIP	8	Ag PLATED	TITLE : VERTICAL SLIDE SWITCH		UNIT : mm	DRWG NO.:	
3	BASE	PHENOLIC RESIN	1	NATURAL	MODEL:		SCALE: 3:1	DWN.	2012-10-28
2	FRAME	STEEL STRIP	1	Ni PLATED	东莞市高迪电子有限公司				CHK'D
1	KNOB	POM	1	BLACK					APPD.
NO.	PARTS	MATERIALS	Q'TY	FINISH					2012-10-28