



MRUSB-5B-ED9x-S347

SHELL鍍層:

TN

NI

NOTES:

1.MATERIAL:

1.1 HOUSING: LCP

1.2 CONTACT: PHOSPHOR BRONZE

1.3 SHELL: BRASS

2.Finish:

2.1 Contact: Plated Gold in Mating Area ;

Gold Plated on Solder Balls ;

Nickel under plated overall

2.2 Shell: Tin or Nickel under Plated surface layer

3.SPECIFICATION:

3.1 CURRENT RATING: 1.0 A MAX

3.2 DIELECTRIC WITHSSTANDING VOLTAGE:

100 V(ac) FOR 1min

3.3 CONTACT RESISTANCE: 30 mΩ MAX.








3.4 INSULATION RESISTANCE: 100 MΩ MIN.

3.5 TOTAL MATING FORCE: 3.57 Kgf MAX.

3.6 TOTAL UNMATING FORCE: 1.0 Kgf MIN.

3.7 LIFE: 10,000 CYCLES

3.8 TEMPERATURE RANGE: -30°C ~ +80°C



P.C.B LAYOUT MOUNTING PATTERN



东莞市高迪电子有限公司

Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD.
ANGEL'S



UNITS

MM

DRAWN BY:
Jack Lu

DATE
07/05/18

CHECKED BY:
Jacky Chen

DATE
07/05/18

APPROVED BY:
Tony Kao

DATE
07/05/18

MAT'L		TITLE	CONNECTOR
FINISH		MODLE	MICRO USB 5BF 牛角型(PH7.15-4.85),無捲邊
SCALE	1 : 1	DWG NO.	MRUSB-5B-ED9x-S347
SHEET NO.	1 of 1	PART NO.	MRUSB-5B-ED9x-S347

ITEM NO.	DESCRIPTION	DRAWN	DATE
1	新增SHELL鍍層選項	Jack	070518