



SPEC:

A. Material:

1. Housing: PA66

2. Terminal:

Base: COPPER ALLOY

Base Plating: Ni 2.0 um

Surface Plating: Sn 3.0 um

B. Electrical Characteristics:

1. Rating: 15A 250V~ (UL, CUL)

10A 250V~ (VDE, CCC, SEMKO, NEMKO, DEMKO, FIMKO, KC)

2. Electric Strength: AC 2,000V FOR ONE MINUTE

3. Insulation Resistance: 100MΩ MIN. AT 500V DC

C. Approvals:

UL, CUL, VDE, CCC, SEMKO, NEMKO, DEMKO, FIMKO, KC

普通公差

COMMON TOLERANCE :

| | |
|---------------|-------|
| UP TO 5 | ±0.20 |
| ABOVE 5 TO 30 | ±0.30 |
| ABOVE 30 | ±0.50 |
| ANGULAR | ±5° |



东莞市高迪电子有限公司

| | | | | | | | | | |
|------|------|----------------------|-------|----------------|------------|-------------------|--|--------------------|---------------|
| REV. | DATE | REVISION DESCRIPTION | ISSUE | 单位 UNIT | mm | 投影 PROJECTED | | 品名 PRODUCT NAME | AC POWER JACK |
| | | | | 绘图 DRAWN BY | 林晓良 | 核对 CHECKED BY | | 型号 MODEL NO. | |
| | | | | 日期 DATE | 19. 08. 12 | 核准 APPROVAL BY | | 料号 PART NO. | KD-AC电源插座 |