





PCB线路板安装图(±0.2)



SPECIFICATIONS

Rating	DC 12V 50mA.			
Insulation Resistance	50 M Ω Min.			
Contact Resistance	100 m Ω Max.			
Operating Force	2	160 $\pm$ 50gf	3	260 $\pm$ 50gf
Operating Life (cycles)	50,000			



电路图

E	TERMINAL	3	PHOSPHOR BRONZE	Ag plated
D	CONTACT	2	SUS	Ag plated
C	COVER	1	PHOSPHOR BRONZE	Ag plated
B	BASE	1	PA6T	Black
A	STEM	1	PPA	White
NO.	DESCRIPTION	QTY	MATERIAL	PLATING

7	新增尺寸	Jack	010318
6	更新侧面尺寸	Jack	112317
5	更新PCB LAYOUT模式及尺寸	Jack	020317
4	更新PCB LAYOUT模式	Jack	011717
3	更新SPEC及材质	Jack	061515
2	更新尺寸标示	Jack	050615
1	新增PIN脚	Jack	020315
ITEM NO.	DESCRIPTION	DRAWN	DATE



东莞市高迪电子有限公司

Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS
OTHERWISE STATED:

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD.
ANGEL'S



UNITS

MM

DRAWN BY:	DATE
Jack Lu	01/03/18
CHECKED BY:	DATE
Jacky Chen	01/03/18
APPROVED BY:	DATE
Tony Kao	01/03/18

MAT'L	TITLE	SWITCH
FINISH	MODLE	TACT SWITCH
SCALE	1 : 1	DWG NO.
SHEET NO.	1 of 1	PART NO.
SIZE	A4	VER
		R7