









select	H(value)	A
	4.5	ø3.5
	5.0	ø3.5
	6.0	ø3.3
	6.5	ø3.3
	7.0	ø3.3
	7.5	ø3.3
	8.0	ø3.3
	8.5	ø3.2
	9.0	ø3.2
	9.5	ø3.1
	10	ø3.1
	10.5	ø3.0
	11	ø3.0
	11.5	ø3.0
	12	ø3.0
	12.5	ø3.0
	13	ø3.0
	15	ø3.0
	16	ø3.0
	17	ø3.0
	18	ø3.0
	19	ø3.0
	20	ø3.0
	21	ø3.0
	22	ø3.0
	23	ø3.0
	24	ø3.0
	25	ø3.0
	26	ø3.0
	27	ø3.0
	28	ø3.0
	29	ø3.0



PCB板开孔尺寸(±0.1)



电路图

SPECIFICATIONS

Rating	DC 12V 50mA.		
Insulation Resistance	50 MΩ Min.		
Contact Resistance	100 mΩ Max.		
Operating Force	2	160 ± 50gf	3 260 ± 50gf
Operating Life (cycles)	50,000		

E	TERMINAL	3	PHOSPHOR BRONZE	Ag plated
D	CONTACT	2	SUS	Ag plated
C	COVER	1	PHOSPHOR BRONZE	Ag plated
B	BASE	1	PA6T	Black
A	STEM	1	PPA	White
NO.	DESCRIPTION	QTY	MATERIAL	PLATING

7	新增尺寸	Jack	010918
6	更新侧面尺寸	Jack	112317
5	更新PCB LAYOUT模式及尺寸	Jack	020917
4	更新PCB LAYOUT模式	Jack	011717
3	更新SPEC及材质	Jack	061515
2	更新尺寸标示	Jack	050615
1	新增PIN编号	Jack	020915
ITEM NO.	DESCRIPTION	DRAWN	DATE



东莞市高迪电子有限公司

Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS
OTHERWISE STATED:

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD.
ANGEL'S



UNITS

MM

DRAWN BY:

Jack Lu

DATE

01/03/18

MAT'L

TITLE

SWITCH

CHECKED BY:

Jacky Chen

DATE

01/03/18

FINISH

MODLE

TACT SWITCH

APPROVED BY:

Tony Kao

DATE

01/03/18

SCALE

1 : 1

DWG NO.

SHEET NO.

1 of 1

PART NO.

SIZE

A4

VER

R7