







Ø (mm)	H (mm)
3.5	4.3
3.5	4.5
3.5	5.0
3.5	5.5
3.5	6.0
3.3	6.5
3.4	7.0
3.3	7.5
3.3	8.0
3.3	8.5
3.1	9.0
3.1	9.5
3.1	10.0
3.0	10.5
3.0	11.0
3.0	11.5
3.0	12.0
3.0	12.5
3.0	13.0
3.0	13.5
3.0	14.0
3.0	14.5
3.0	15.0
3.0	15.5
3.0	16.0
3.0	17.0



SPECIFICATIONS

Rating	DC 12V 50mA.			
Insulation Resistance	50 MΩ Min.			
Contact Resistance	100 mΩ Max.			
Operating Force	2	160 ± 50gf	3	260 ± 50gf
Operating Life (cycles)	50,000			

E	TERMINAL	3	PHOSPHOR BRONZE	Ag plated
D	CONTACT	2	SUS	Ag plated
C	COVER	1	PHOSPHOR BRONZE	Ag plated
B	BASE	1	PA6T	Black
A	STEM	1	PPA	White
NO.	DESCRIPTION	QTY	MATERIAL	PLATING

7	新增尺寸	Jack	010318
6	更新侧面尺寸	Jack	112317
5	更新PCB LAYOUT模式及尺寸	Jack	020317
4	更新PCB LAYOUT模式	Jack	011717
3	更新SPBC及材质	Jack	061515
2	更新尺寸标示	Jack	050615
1	新增PIN脚	Jack	020315
ITEM NO.	DESCRIPTION	DRAWN	DATE



东莞市高迪电子有限公司

Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD.
ANGEL'S



UNITS

MM

DRAWN BY:

Jack Lu

DATE

01/03/18

MAT'L

TITLE

SWITCH

CHECKED BY:

Jacky Chen

DATE

01/03/18

FINISH

MODLE

TACT SWITCH

APPROVED BY:

Tony Kao

DATE

01/03/18

SCALE

1 : 1

DWG NO.

PART NO.

SHEET NO.

1 of 1

SIZE

A4

VER

R7