






ϕ (mm)	H (mm)
3.5	4.3
3.5	4.5
3.5	5.0
3.5	5.5
3.5	6.0
3.3	6.5
3.4	7.0
3.3	7.5
3.3	8.0
3.3	8.5
3.1	9.0
3.1	9.5
3.1	10.0
3.0	10.5
3.0	11.0
3.0	11.5
3.0	12.0
3.0	12.5
3.0	13.0
3.0	13.5
3.0	14.0
3.0	14.5
3.0	15.0
3.0	15.5
3.0	16.0
3.0	17.0




$0.25 \pm 0.1\text{mm}$
Travel



P. C. B LAYOUT



CIRCUIT



SPECIFICATIONS

Rating	DC 12V 50mA.		
Insulation Resistance	50 M Ω Min.		
Contact Resistance	100 m Ω Max.		
Operating Force	2	160 $\pm$ 50gf	3 260 $\pm$ 50gf
Operating Life (cycles)	50,000		

E	TERMINAL	3	PHOSPHOR BRONZE	Ag plated
D	CONTACT	2	SUS	Ag plated
C	COVER	1	PHOSPHOR BRONZE	Ag plated
B	BASE	1	PA6T	Black
A	STEM	1	PPA	White
NO.	DESCRIPTION	QTY	MATERIAL	PLATING

7	新增尺寸	Jack	010918
6	更新画面尺寸	Jack	112317
5	更新PCB LAYOUT模式及尺寸	Jack	020917
4	更新PCB LAYOUT模式	Jack	011717
3	更新SPBC及材質	Jack	061515
2	更新尺寸標示	Jack	050615
1	新增PIN編號	Jack	020915
ITEM NO.	DESCRIPTION	DRAWN	DATE



东莞市高迪电子有限公司

Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS
OTHERWISE STATED:

Up to 5 ± 0.2
Above 5 ~ 15 ± 0.3
Above 15 ~ 30 ± 0.4
Above 30 ~ 50 ± 0.5
Angle $\pm 0.3^\circ$

3RD.
ANGEL'S



UNITS

MM

DRAWN BY:

Jack Lu

DATE

01/03/18

CHECKED BY:

Jacky Chen

DATE

01/03/18

APPROVED BY:

Tony Kao

DATE

01/03/18

MAT'L

FINISH

SCALE

SHEET NO.

TITLE

MODLE

DWG NO.

PART NO.

SWITCH

TACT SWITCH

SIZE

A4

VER

R7