



SCHEMATIC (NON-SHORTING)

Rating: UL/CUL: 5A 125/250VAC 1/2 HP 40T125
 ENEC, KC: 5(2)A 125/250VAC 40T125
 CQC: 5(2)A 125/250VAC 40T125 PTI175

Electrial life: 50000 cycles

Mechanical life: 1000000 cycles

IP code: IP40

注：“*”□表示关键尺寸(4个).

				TOLERANCE UNLESS SPECIFIED					
7	PLASTIC HANDLE	PA66	1	BLACK					
6	CONTACT	AG	1	NATURAL	WITHIN 1.5mm : ±0.1mm	A		初版	
5	SHRAPNEL	PBS	1	NATURAL	OVER 1.5mm : ±0.2mm	ISSUE	DATE	DESCRIPTIONS OF REVISION	APPD.
4	KNOB	PA9T	1	BLACK	TITLE : MICRO SWITCH		UNIT : mm	DRWG NO.:	
3	COVER	PA66	1	BLACK	MODEL:		SCALE: 3:1	DWN.	刘工
2	BASE	PA9T	1	BLACK				CHK'D	戴海明
1	TERMINAL	BRASS STRIP	3	Ag PLATED				APPD.	林小姐
NO.	PARTS	MATERIALS	Q'TY	FINISH	東莞市高迪電子有限公司				