



SPECIFICATIONS

Electrical:







- 1.Current Rating: 1.0A / contact terminal
- 2.Voltage Rating: 30V DC
- 3.Contact Resistance: 50 milliohms Max
- 4.Dielectric Withstanding Voltage:
300 V AC AT Sec Level
- 5.Insulation Resistance: 100 MEGA ohms Min

Mechanical:

- 1.Connector Mate and Unmate Force
Mate force: 3.0 kgf (Max)
Unmate force: 0.7 kgf (Min)
- 2.Terminal Retention: 0.5 kgf (Min)

Material:

- 1.Housing:
High Temperature Thermal Plastics,
UL 94V-0 , LCP , Black
 - 2.Contact: Phosphor Bronze
 - 3.Shell: Brass
- Finish:**
- 1.Contact: Plated Gold in Mating Area ;
Tin Plated on Solder Balls
Nickel under plated overall
 - 2.Shell: Nickel under Plated surface layer



P.C.B LAYOUT MOUNTING PATTERN



东莞市高迪电子有限公司

Dong Guan KDRR Electronic Switch Jack Co., Ltd.

TOLERANCE UNLESS
OTHERWISE STATED :

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD.
ANGEL'S



UNITS

MM

DRAWN BY: Jack Lu
CHECKED BY: Jacky Chen
APPROVED BY: Tony Kao

DATE
06/16/14
06/16/14
06/16/14

MAT'L	TITLE	CONNECTOR
FINISH	MODLE	MINI USB 5BF 4脚 DIP 端子长 1.9mm
SCALE	DWG NO.	MUSB-5B-FM0F-S175
SHEET NO.	PART NO.	MUSB-5B-FM0F-S175

ITEM NO.	DESCRIPTION	DRAWN	DATE
3	更新contact材質	Jack	061614
2	更新contact鍍層鍍Tin	Jack	122413
1	更新contact鍍層鍍金	Jack	102813