




CAD FILE:



SCHEMATIC (NON-SHORTING)

額定電流、電壓 RATING

16A 250VAC μ 1E4 T85
12A 250VAC/15A 125VAC

接觸電阻 CONTACT RESISTANCE

 $\leq 20m\Omega$

絕緣電阻 INSULATION RESISTANCE

 $\geq 100M\Omega$

介電強度 DIELECTRIC INTENSITY

 $\geq 1250VAC/3S$

電器壽命 ELECTRICAL LIFE

 $\geq 10,000$ Cycles

注：“*”口表示关键尺寸(4个).

NO.	PARTS	MATERIALS	Q'TY	FINISH	TOLERANCE UNLESS SPECIFIED				
						A	DATE	DESCRIPTIONS OF REVISION	APPD.
7	PLASTIC HANDLE	PA66	1	BLACK	WITHIN 1.5mm : $\pm 0.1mm$ OVER 1.5mm : $\pm 0.2mm$	ISSUE		初版	
6	CONTACT	AG	1	NATURAL					
5	SHRAPNEL	PBS	1	NATURAL	TITLE : MICRO SWITCH			DRWG NO.:	
4	KNOB	PA9T	1	BLACK					
3	COVER	PA66	1	BLACK	MODEL:			SCALE: 3:1	
2	BASE	PA9T	1	BLACK					
1	TERMINAL	BRASS STRIP	3	Ag PLATED	東莞市高迪電子有限公司			DWN. 刘工	2008.6.8
								CHK'D 戴海明	2008.6.8
								APPD. 林小姐	2008.6.8