



CAD FILE:



SCHEMATIC (NON-SHORTING)

額定電流、電壓 RATING

16A 250VAC μ 1E4 T85
12A 250VAC/15A 125VAC

接觸電阻 CONTACT RESISTANCE

 $\leq 20m\Omega$

絕緣電阻 INSULATION RESISTANCE

 $\geq 100M\Omega$

介電強度 DIELECTRIC INTENSITY

 $\geq 1250VAC/3S$

電器壽命 ELECTRICAL LIFE

 $\geq 10,000$ Cycles

注: "*"口表示关键尺寸(4个).

NO.	PARTS	MATERIALS	Q'TY	FINISH	TOLERANCE UNLESS SPECIFIED				
						A	DATE	DESCRIPTIONS OF REVISION	APPD.
7	PLASTIC HANDLE	PA66	1	BLACK	WITHIN 1.5mm : $\pm 0.1mm$ OVER 1.5mm : $\pm 0.2mm$			初版	
6	CONTACT	AG	1	NATURAL					
5	SHRAPNEL	PBS	1	NATURAL					
4	KNOB	PA9T	1	BLACK					
3	COVER	PA66	1	BLACK					
2	BASE	PA9T	1	BLACK					
1	TERMINAL	BRASS STRIP	3	Ag PLATED					
					TITLE : MICRO SWITCH		UNIT : mm	DRWG NO.:	
					MODEL:		SCALE: 3:1	DWN.	刘工
								CHK'D	戴海明
								APPD.	林小姐
									2008.6.8
									2008.6.8
									2008.6.8

東莞市高迪電子有限公司