



SPECIFICATIONS

- (1) LIFE TEST: 10000 cycles at a speed of 15-18 cycles
- (2) CONTACT RESISTANCE: 100mΩmax
- (3) INSULATION RESISTANCE: 100MΩmin
- (4) DIELECTRIC STRENGTH: 250V AC FOR 1MIN
- (5) OPERATING TEMPERATURE: -16°C - +60°C
- (6) RATING: 0.1A 30V DC
- (7) FUNCTION: 2P2T
- (8) TIMING: NON-SHORTING
- (9) OPERATING FORCE: 180gf ± 50gf

8				TOLERANCE UNLESS SPECIFIED				
7								
6				WITHIN 1.5mm : ±0.1mm	A	2016-10-14	初版	
5	SPRING	SUS304	1	NATURAL	ISSUE	DATE	DESCRIPTIONS OF REVISION	APPD.
4	CAM STICK	SUS304	1	NATURAL	TITLE : VERTICAL PUSH SWITCH			UNIT : mm
3	CASE	PA66/BRASS STRIP	1	GREY/Ag PLATED	MODEL:			SCALE: 5:1
2	COVER	PA66+15%F.G	1	BLACK	东莞市高迪电子有限公司 DONGGUANGAODIELECTRONICS CO.,LTD.			DRWG NO.:
1	KNOB	PA66+15%F.G/PBS STRIP	1	BLACK/Ag CLAD				DWN.
NO.	PARTS	MATERIALS	Q'TY		CHK'D	2016-10-14	APPD.	